

360 Gold Telemetry Load Links suitable for use in Zone 1

Our answer to measurement of Tensile load in heavy industrial applications

All our load links are manufactured from anodized aerospace grade aluminium, allied with our full O-ring sealing gives ingress protection of IP67.

Supplied with the X24-HD, a highly configurable ATEX/IECEX handheld display. With a range up to 800 metres, this allows wireless remote viewing in the hazardous areas.

Units available from 2.5 Tonne to 500 Tonne

Units from 2.5 to 50 Tonne are supplied in an IP67 transit case,

75 to 500 Tonne units supplied in a hinged wooden transit crate



360 Gold Telemetry Load Links suitable for use in Zone 1

Our answer to measurement of Tensile load in heavy industrial applications

SIZE	A	B	C	D	E	WEIGHT
2.5 Tonne	23	215	120	270	25	2.4
5 Tonne	27	227	120	292	32	2.6
12.5 Tonne	44	226	130	324	50	5.3
25 Tonne	55	240	134	360	70	7.1
35 Tonne	62	290	140	440	70	9.4
55 Tonne	78	298	163	476	85	15.0
75 Tonne	86	306	190	500	100	17.0
100 Tonne	100	346	194	556	124	26.1
150 Tonne	120	396	244	680	127	47.1
200 Tonne	132	442	280	784	150	79.0
250 Tonne	146	466	300	844	150	TBA
300 Tonne	160	582	400	1000	150	TBA
400 Tonne	180	614	400	1098	200	TBA
500 Tonne	190	600	490	1100	200	TBA

All sizes in mm
Please confirm any critical dimension before ordering

